

# Kerotest Needle and Gauge Valves

## N20 In-Line Union Bonnet Needle Valve

### Specifications:

- Female Pipe Ends per ANSI B1.20.1
- Socket Weld Ends per ANSI B16.11
- Max. Working Pressure 10,000 PSI @ 100 ° F
- Max. Temperature 750 ° F

Size	End-to-End	C/L to Top ( Open )	Handle	Weight ( lbs )
1/4 "	2 - 1/16 "	3 - 3/8 "	3 "	0.90
3/8 " and 1/2 "	2 - 1/2 "	3 - 9/16 "	3 "	1.25
3/4 "	3 "	4 - 5/32 "	4 "	2
1 "	3 - 3/4 "	4 - 5/32 "	4 "	3.30

### Ordering Code:

Type		1/4" Part No.	3/8" Part No.	1/2" Part No.	3/4" Part No.	1" Part No.
Female-NPT	Carbon Steel	P-0N20-49-002	P-0N20-49-003	P-0N20-49-004	P-0N20-49-006	P-0N20-49-008
	316 Stainless	T-0N20-49-002	T-0N20-49-003	T-0N20-49-004	T-0N20-49-006	T-0N20-49-008
Socket Weld	Carbon Steel	P-0N20-96-002	P-0N20-96-003	P-0N20-96-004	P-0N20-96-006	P-0N20-96-008
	316 Stainless	T-0N20-96-002		T-0N20-96-004	T-0N20-96-006	T-0N20-96-008

**For H<sub>2</sub>S Service, Add -A07 to 316SS Part No.**



**Kerotest Manufacturing Corp.**

5500 Second Avenue

Pittsburgh, PA 15207

Phone: 412-521-7688 Fax: 412-521-5990