

Pressure transmitter Model A-10

Modelcode type: A-10

Item number: 70109737

MEASURING RANGE

Pressure range -30 InHg...0 psi

Overload Safety 3 times

Vacuum tightness yes

OUTPUT SIGNAL

Output signal 4 ... 20 mA, 2-wire

Permissible load in ?

Settling time < 1 ms

POWER SUPPLY

Power supply 8...30 V DC

Total current consumption Current signal, max. 25 mA

ACCURACY INFORMATION

non-linearity 0.5% BFSI

Long-term drift ? ±0.1 % of span

OPERATING ENVIRONMENT CONDITIONS

Temperature range of medium 0...+80 °C

Permissible ambient temperature

Shock resistance

Service life 100 million load cycle

MATERIALS

Wetted parts

Non-wetted parts

PROCESS CONNECTION

Process Connection 1/4 NPT

ELECTRICAL CONNECTION

Electrical Connection valve connector, size A

Ingress Protection

pin assignment el. connection U+=1, U-=2

ELECTRICAL SAFETY

Short-circuit resistance S+ vs. U-

Reverse polarity protection



Pressure transmitter Model A-10

Modelcode type: **A-10**

Item number: **70109737**

Insulation voltage DC 500 V

CE-CONFORMITY, APPROVALS AND CERTIFICATES

CE conformity

Approvals cULus